

H33NBG



General information:

Cut Resistant Level 5 Seamless Nitrile Coated Gloves Blended with Glass Fiber. Sandy Finish.

Sizes:

7, 8, 9 & 10



Description:

This glove series provides durable hand protection and supreme cut resistance, with outstanding dexterity. 13 gauge gloves are made with Glass and UHMWPE based blended yarn and a Nitrile coated palm and finger tips offer increased grip, chemical & mechanical resistance

Materials:

Liner blended with UHMWPE, Glass, Polyamide, Polyester & Spandex Fiber. Coating with NBR compound, Colour coded Overlock binding polypropylene yarn 07 – Red, 08 – Yellow, 09 – Brown – 10 – Black

Feature:

- The optimal combination of cut resistance, comfort and dexterity. These premium gloves use innovative technology for improved cut resistance, excellent flexibility and a higher level of user comfort
- Open back configuration provides superior ventilation.
- Ergonomically correct design conforms snugly to the natural shape of the hand, increasing comfort and reducing hand fatigue.
- Colour coded overlock binding helps to identify different sizes (07 – Red, 08 – Yellow, 09 – Brown – 10 – Black)
- Nitrile dipped palm provides excellent puncture and abrasion resistance properties, also provide assistance to handling chemicals and oils.
- Level 5 Blade cut resistance gloves makes easier to work with sharp edged objects e.g. Machine blade, glass, installing barb wire Fence etc

Performances:

This glove complies with the European directive 89/686, notably regarding ergonomics, innocuousness, comfort, ventilation and flexibility, with EN 420:2003+A1:2009 Dexterity level 5 & EN 388:2003 (4 5 4 3) EC – Type

Examination Certificate for the final product by CTC (0075) 4 rue Hermann Frenkel 69367 Lyon cedex 07 France



EN 388
 4: Resistance to abrasion (from 0 to 4)
 5: Resistance to cut (from 0 to 5)
 4: Resistance to tear (from 0 to 4)
 3: Resistance to puncture (from 0 to 4)



Technical specification:

Construction	Liner	Gauge	Total weight/pair (g)	Nitrile consumption weight/pair (g)
Seamless	Glass, UHMWPE fibre based liner	13	91 (Size 9)	38 (Size 09)
Overlock binding	Coating Material	Thickness of palm (mm)	Finishing	Packaging
Polypropylene yarn	100% Nitrile dipped	1.5	Palm dipped smooth finish	12 pairs in a primary packet 12 packets in a carton

Applications:

Automotive Aftermarket

- Chassis assembly, body trimming
- Foundry operations

Machinery and Equipment

- Handling materials with sharp or rough edges
- Handling metal sheets & panels
- Handling parts in high heat areas
- Handling parts with sharp, rough edges



Packaging Instruction:

1 Dozen Pairs in a polybag, 10 poly bags in a carton, 120pairs/Carton

Limits to use

Do not use this glove out of its usage specifications defined in the instructions above. This glove does not contain substance known as being carcinogenic, neither toxic, nor likely to cause allergies to the sensitive people.

Instructions for storage:

Store in a cool, dry place; away from frost and light in their original packaging.

Instructions for cleaning:

No specific cleaning or maintenance for this type of glove.

Warning

Gloves not to be worn when there is a risk of entanglement by moving parts of machines

MANUFACTURER ADDRESS

Mallcom (India) Limited
 Mallcom Tower
 EN 12, Salt Lake, Sec V
 Kolkata – 700091
 West Bengal, India