

P25NGA

Features

- 15 gauge-polyester seamless liner.
 Single layered smooth finish nitrile glove
- Excellent abrasion resistant
- Good comfortable fit.
- Superior grip on oily surfaces
- Ventilated back providing better breathability.
- Can be available with different coloured elasticized rib.



Instructions for Use

Mechanics, Packaging, Handling oiled mechanical parts, Metal working, Forestry operations, Handling construction materials, mining industry.

Limits to use

Do not use this glove out of its usage specifications defined in the instructions above. This glove does not contain substance known as being carcinogenic, neither toxic, nor likely to cause allergies to the sensitive people.

Instructions for storage

Keep in its original packing away from light and sunlight.



Features

• Sizes:	07,08,09, 10
• Shell material:	Polyester
• Glove Colour:	Grey
• Liner	White
• Gauge	15

Instructions for Cleaning

No special cleaning or maintenance is recommended for these types of gloves.

Performances

This glove complies with the European directive 89/686, notably regarding ergonomics, innocuousness, comfort, ventilation and flexibility, with EN420:2003 + A1: 2009, EN388:2003 (4.1.3.1)

EN 388: 2003 Protective gloves against mechanical risks (Levels obtained on the palm)



- 4: Resistance to abrasion (from 0 to 4)
- 1: Resistance to cut (from 0 to 5)
- 3: Resistance to tear (from 0 to 4)
- 1: Resistance to puncture (from 0 to 4)